NSN 5935-01-259-3625

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-259-3625 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Black **Body Style:** Threaded bushing mounted **Overall Length:** 1.670 inches **Mounting Bushing Length:** 0.520 inches **Body Length:** 1.220 inches **Overall Diameter:** 0.500 inches **Bushing Accommodation Hole Shape:** Round w/flat **Maximum Voltage Rating In Volts:** 2500.0 dc **Accommodated Finger Type:** Banana spring single finger **Finger Accommodation Diameter:** 0.166 inches single finger **Finger Accommodation Length:** 0.562 inches single finger **Bushing Thru-hole Accommodation Length:** 0.350 inches **Bushing Thru-hole Accommodation Width:** 0.380 inches **Current Rating In Amps:** 15.0 **Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches

Terminal Type:

Wire wrap

NSN 5935-01-259-3625

Tip Jack - Page 2 of 2



Material:
Plastic, polycarbonate insulator
Material:
Plastic polycarbonate insulator
Precious Material And Location:
Contact and terminal surfaces gold
Precious Material:
Gold
Surface Treatment:
Nickel bushing
Surface Treatment:
Nickel bushing
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A03400