# NSN 5935-01-259-3666

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-259-3666 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.010 inches **Overall Height:** 1.158 inches **Overall Width:** Between 4.300 inches and 4.330 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock resistant and thermal shock resistant Center To Center Distance Between Mounting Facilities Parallel To Height: 0.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 3.870 inches and 3.880 inches **Distance From Mounting Shoulder To Front Face:** Between 0.615 inches and 0.630 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 71c15 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end 2nd contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches

**Terminal Location:** 

Back single mating end all contact groupings

# NSN 5935-01-259-3666

Electrical Receptacle Connector - Page 2 of 3



### **Contact Material:**

Copper alloy single mating end all contact groupings

#### **Contact Surface Treatment:**

Gold single mating end all contact groupings and copper single mating end all contact groupings

### **Insert Material:**

Plastic single mating end

### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end all contact groupings

### **Terminal Type:**

Crimp single mating end all contact groupings

### **Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end all contact groupings

### **Shell Material:**

Aluminum alloy

### **Shell Surface Treatment:**

Nickel

### **Shell Surface Treatment Specification:**

Mil-c-26074, cl 3 military specification single treatment response

### **Shell Material Specification:**

Qq-a-591 federal specification single material response

#### **Unable To Decode:**

Unable to decode and unable to decode

### **Included Contact Quantity:**

56 single mating end 2nd contact grouping

### **Included Contact Type:**

Round socket single mating end 2nd contact grouping

### **Special Features:**

Connector does not come with backshell, screws, and washers

### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.071 gold grains, troy

### **Precious Material:**

Gold

### **Thread Series Designator:**

Unc

### Shelf Life:

N/a

### **Unit Of Measure:**

--

### Demilitarization:

No

### Fiig:

A039b0

# NSN 5935-01-259-3666

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.