NSN 5935-01-259-5485

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-259-5485

Body Style:
Straight shape, external coupling
Overall Length:
1.662 inches
Overall Height:
2.000 inches
Overall Width:
2.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.562 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.562 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
28-21 single mating end
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold

Test Data Document:

81343-ms3402 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5935-01-259-5485

Electrical Receptacle Connector - Page 2 of 2



Spec	ifica	tion	Data:
------	-------	------	-------

81343-ms3402 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.