NSN 5935-01-259-6391

Electrical Receptacle Connector - Page 1 of 2



Body Style:
Straight type
Overall Length:
3.426 inches
Overall Width:
0.355 inches
Body Height:
0.375 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
92 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end and glass fiber single
mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290,
class 2 federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f or ty gdi-30f military specification all material responses single mating end or mil-m-24519, ty gpt-30f or ty gst-40f military specification all material responses single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

View Online at https://aerobasegroup.com/nsn/5935-01-259-6391

NSN 5935-01-259-6391

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.092 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.