NSN 5935-01-259-7021

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-259-7021

Body Style:

Rectangular shape

Overall Length:

Between 1.320 inches and 1.335 inches

Overall Height:

0.371 inches

Overall Width:

0.215 inches

Environmental Protection:

Heat resistant and cold resistant and salt water resistant and pressure proof and moisture resistant and vibration resistant and shock resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

31 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

End Application:

Third generation gyro

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 1, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Included Contact Quantity:

31 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

NSN 5935-01-259-7021

Electrical Receptacle Connector - Page 2 of 2



Unit	Of	Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.