Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-259-8745

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
0.656 inches
Overall Diameter:
0.625 inches
Distance From Mounting Shoulder To Front Face:
0.593 inches
Mounting Facility Thickness:
0.125 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
40393 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
80.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
6 and 24
Thread Size:
0.500 inches and 0.562 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
,, , , , , , , , , , , , , , , , , , ,

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

### Insert Material:

Plastic single mating end

# Terminal Type:

Solder well single mating end single contact grouping

## Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium and chromate

# Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

### Included Contact Quantity:

3 single mating end single contact grouping

### Bushing Accommodation Hole Shape:

Round w/flat

### Included Contact Type:

Round socket single mating end single contact grouping

### Precious Material And Location:

Contact surfaces gold and contact surfaces silver

## Precious Material And Weight:

 $0.003 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.003 \ \text{silver grains}, \ \text{troy}$ 

Precious Material:

Gold and silver

#### Thread Series Designator:

Special acme and unef

#### Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A039b0