Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-259-9548

Body Sty	le:
Straight ty	pe
Overall L	ength:
4.295 inch	nes
Overall W	/idth:
0.390 inch	nes
Unthread	ed Mounting Hole Diameter:
Between (	0.122 inches and 0.127 inches
Distance	Between Mounting Facility Centers:
3.975 inch	nes
Mating Er	nd Quantity:
1	
Contact F	Removability:
Nonremov	vable single mating end single contact grouping
Contact N	Iaximum Current Rating In Amps:
3.0 single	mating end single contact grouping
Polarizati	on Method:
Mating en	d
Connecto	or Locking Method:
Friction	
Terminal	Location:
Back singl	le mating end single contact grouping
Contact N	Naterial:
Copper all	loy single mating end single contact grouping
Contact S	Surface Treatment:
Gold singl	e mating end single contact grouping
Insert Ma	terial:
Plastic pol	lyester single mating end
Contact S	Surface Treatment Specification:
Mil-g-452(	04, type 1, gr c, cl 00 military specification single treatment response single mating end single contact grouping
Terminal	Туре:
Pin single	mating end single contact grouping
Contact M	Naterial Specification:
Qq-c-530	federal specification single material response single mating end single contact grouping
Included	Contact Quantity:
60 single i	mating end single contact grouping
Precious	Material And Location:
Contact si	urfaces gold
Precious	Material And Weight:
0.060 gold	d grains, troy
Precious	Material:
Gold	

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.