

View Online at <https://aerobasegroup.com/nsn/5935-01-260-2365>

**Thread Direction:**

Right-hand

**Body Style:**

Right angle type

**Overall Length:**

Between 3.905 inches and 3.932 inches

**Overall Width:**

Between 0.663 inches and 0.679 inches

**Body Height:**

Between 0.248 inches and 0.256 inches

**Environmental Protection:**

Humidity resistant and shock resistant and vibration resistant

**Threaded Device Type:**

Mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Friction

**End Application:**

4920-01-149-9950 collection unit

**Thread Size:**

1.6 millimeters

**Thread Pitch In Millimeters:**

0.35

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end and glass single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, gr c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping and mil-c-14550, cl x military specification 3rd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14 military specification all material responses single mating end

**Thread Tolerance Class:**

6g external

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

65 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.065 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Iso m

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.