NSN 5935-01-260-2841

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-260-2841

Body Style:
Right angle type
Overall Length:
2.190 inches
Overall Height:
0.519 inches
Overall Width:
0.270 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant
Distance Between Mounting Facility Centers:
2.050 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-750, composition a federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14f, type sdgf military specification single material response single mating end

Included Contact Quantity:

36 single mating end single contact grouping

NSN 5935-01-260-2841

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Board mounting
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.036 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-m-14f spec.