Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-260-5261

Thread Direction: Right-hand Body Style: Straight shape, external coupling Overall Length: 34.16 millimeters Overall Diameter: 37.50 millimeters Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 19-11 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: 28.0 millimeters 1.00 Thread Size: 28.0 millimeters 1.00 Thread Nameters 1.00 Ensert Position In Millimeters: 1.00 Solid Connector Locking Method: 28.0 millimeters 1.00 Thread Size: 28.0 millimeters 1.00 Ensert Position In Millimeters: 1.00
Body Style: Straight shape, external coupling Overall Length: 34.16 millimeters Overall Diameter: 37.50 millimeters Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 19-11 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 11.0.0 and 250.0 Shell Type: Solid Connector Locking Method: Potent Thread Size: 28.0 millimeters 19.0 Thread Size: 28.0 millimeters 1.00 Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Straight shape, external coupling Overall Length: 34.16 millimeters Overall Diameter: 37.50 millimeters Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 19-11 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Polerit Thread Size: 28.0 millimeters 10.0 Anting End Size: 28.0 millimeters 10.0 Contact In Millimeters: 10.0 Back single mating end single contact grouping
Overall Length:34.16 millimetersOverall Diameter:37.50 millimetersThreaded Device Type:Back shellMating End Quantity:1Contact Position Arrangement Style:19-11 single mating endContact Removability:Removable single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:11.0.0 and 250.0Shell Type:SolidConnector Locking Method:DetentThread Size:28.0 millimeters10.0Thread Pitch In Millimeters:10.0LongSolidContaction:DetentSolidChread Size:28.0 millimetersThread Pitch In Millimeters:10.0Enters10.0Contaction:Back single mating end single contact grouping
34.16 millimeters Overall Diameter: 37.50 millimeters Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 19-11 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 11.0.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Thread Size: 28.0 millimeters Thread Size: 10.0 Aread Pitch In Millimeters: 1.0.0 Terminal Location: Back single mating end single contact grouping
Overall Diameter:37.50 millimetersThreaded Device Type:Back shellMating End Quantity:1Contact Position Arrangement Style:19-11 single mating endContact Removability:Removable single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:110.0 and 250.0Shell Type:SolidConnector Locking Method:Lage mail28.0 millimeters17.0 millimeters19.0 millimeters10.0 millimeters<
37.50 millimeters Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 19-11 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Thread Size: 28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 19-11 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Thread Size: 28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 19-11 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Thread Size: 28.0 millimeters: 1.00 Thread Pitch In Millimeters: 1.00 Enterninal Location: Back single mating end single contact grouping
Mating End Quantity: 1 Contact Position Arrangement Style: 19-11 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Thread Size: 28.0 millimeters 1.00 Thread Pitch In Millimeters: 1.00 Earminal Location: Back single mating end single contact grouping
1 Contact Position Arrangement Style: 19-11 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Connector Locking Method: Detent Thread Size: 28.0 millimeters Haread Size: 1.00 Terminal Location: Back single mating end single contact grouping
Contact Position Arrangement Style:19-11 single mating endContact Removability:Removable single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:110.0 and 250.0Shell Type:SolidConnector Locking Method:DetentThread Size:28.0 millimeters:1.00Thread Pitch In Millimeters:1.00Back single mating end single contact grouping
19-11 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Thread Size: 28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: Insert Position In Deg: Into and 250.0 Shell Type: Solid Shell Type: Solid Connector Locking Method: Detent Detent Thread Size: 28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Thread Size: 28.0 millimeters Thread Pitch In Millimeters: 1.00 Ferminal Location: Back single mating end single contact grouping
Polarization Method:Keyway or multiple keywayInsert Position In Deg:110.0 and 250.0Shell Type:SolidConnector Locking Method:DetentThread Size:28.0 millimetersThread Pitch In Millimeters:1.00Terminal Location:Back single mating end single contact grouping
Keyway or multiple keyway Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Thread Size: 28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Insert Position In Deg: 110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Thread Size: 28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
110.0 and 250.0 Shell Type: Solid Connector Locking Method: Detent Thread Size: 28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Shell Type:SolidConnector Locking Method:DetentDetentStread Size:28.0 millimetersThread Pitch In Millimeters:1.00Terminal Location:Back single mating end single contact grouping
Solid Connector Locking Method: Detent Thread Size: 28.0 millimeters 28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Connector Locking Method: Detent Thread Size: 28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Detent Thread Size: 28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Thread Size: 28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
28.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
1.00 Terminal Location: Back single mating end single contact grouping
Terminal Location: Back single mating end single contact grouping
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Chall Matarial
Shell Material:
Aluminum alloy

NSN 5935-01-260-5261

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6g external

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

lso m

Specification Data:

81349-dod-c-38999/49 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.