

View Online at <https://aerobasegroup.com/nsn/5935-01-260-6505>

**Thread Class:**

2a and 2a and 2b

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape w/flange

**Overall Length:**

1.234 inches

**Overall Height:**

1.062 inches

**Overall Width:**

1.062 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.812 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.812 inches

**Distance From Mounting Shoulder To Front Face:**

0.660 inches

**Threaded Device Type:**

Coupling facility and mounting hole

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Sma 2nd mating end

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

335.0 all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

24 and 36 and 40

**Thread Size:**

0.625 inches and 0.250 inches and 0.112 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification 1st treatment response all mating ends single contact grouping and mil-c-14550, cl 4 military specification 2nd treatment response all mating ends single contact grouping

**Contact Material Specification:**

Qq-c-530, cond ht federal specification single material response all mating ends single contact grouping

**Shell Material:**

Steel comp 303

**Shell Surface Treatment:**

Passivate

**Shell Surface Treatment Specification:**

Qq-p-35, type 1 federal specification single treatment response

**Shell Material Specification:**

Ams-5640 assn standard single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response all mating ends

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef and uns and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.