Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-260-8612

| View Online at https://aerobasegroup.com/nsn/5935-01-260-8612 |
|---|
| Body Style: |
| Right angle type |
| Overall Length: |
| 1.260 inches |
| Body Height: |
| 0.300 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.100 inches |
| Distance Between Mounting Facility Centers: |
| 1.100 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Shell |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Side single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Glass single mating end and plastic polyester single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification 1st treatment response single mating end single contact grouping |
| Terminal Type: |
| Pin single mating end single contact grouping |
| Included Contact Quantity: |
| 10 single mating end single contact grouping |
| Included Contact Type: |
| Flat pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.010 gold grains, troy |
| Precious Material: |
| |

Gold

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.