

View Online at <https://aerobasegroup.com/nsn/5935-01-260-9394>

Body Style:

Right angle type

Overall Length:

1.200 inches

Overall Width:

0.200 inches

Body Height:

0.240 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

2.5 single mating end 1st contact grouping

Polarization Method:

Contact

Connector Locking Method:

Friction

Terminal Location:

Side single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Copper alloy single mating end 1st contact grouping and nickel single mating end 1st contact grouping and gold single mating end 1st contact grouping

Insert Material:

Plastic polyphenylene single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-c-14550 military specification 1st treatment response single mating end 1st contact grouping and mil-p-27418 military specification 2nd treatment response single mating end 1st contact grouping and mil-g-45204 military specification 3rd treatment response single mating end 1st contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end 1st contact grouping

Contact Material Specification:

Qq-c-330 federal specification single material response single mating end 1st contact grouping

Insert Material Specification:

Mil-p-46174 military specification all material responses single mating end

Included Contact Quantity:

23 single mating end 1st contact grouping

Included Contact Type:

Round pin single mating end 1st contact grouping

Special Features:

Contact in position 24 omitted

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.023 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-c-14550 spec.