NSN 5935-01-260-9395

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-260-9395 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type **Overall Length:** 7.590 inches **Overall Height:** 0.930 inches **Overall Width:** 0.400 inches **Environmental Protection:** Shock resistant and vibration resistant and heat resistant and humidity resistant **Distance Between Mounting Facility Centers:** 7.466 inches **Board Accommodated Length:** 7.020 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** 0.086 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Connector Locking Method:** Friction **End Application:** 4935-01-207-5355 test station, guided missile system Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:**

Contact Material:

Copper alloy single mating end single contact grouping

Back single mating end single contact grouping

NSN 5935-01-260-9395

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Glass single mating end and plastic polyamide single mating end

Terminal Type:

Wire wrap single mating end single contact grouping

Included Contact Quantity:

88 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.088 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0