NSN 5935-01-261-1521

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-261-1521

Thread Class: 2a and 2a and 2b **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 31.5 millimeters **Overall Height:** 33.3 millimeters **Overall Width:** 33.3 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: Between 24.6 millimeters and 26.9 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 24.6 millimeters and 26.9 millimeters **Distance From Mounting Shoulder To Front Face:** 20.9 millimeters **Threaded Device Type:** Back shell and coupling facility and hub **Mating End Quantity:** 12 **Contact Position Arrangement Style:** 16-35 single mating end **Polarization Method:** Keyway or multiple keyway and key, multiple key groove **Insert Position In Deg:** 116.0 and 160.0 and 191.0 and 311.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 10 and 32 and 18 **Thread Size:** 25.0 millimeters and 1.188 inches **Thread Pitch In Millimeters:** 1.00 and 1.00 **Shell Material:** Aluminum alloy or zinc

Shell Surface Treatment:

Cadmium and chromate and zinc

NSN 5935-01-261-1521

Electrical Receptacle Connector Body - Page 2 of 2



Shell	Surface	Treatment 9	Specification:
OHEH	Juliace	i i cauliciii v	Juccilloanoii.

Qq-p-416 ty ii, cl 3 federal specification single treatment response

Thread Tolerance Class:

6g external and 6h external

Special Features:

17-35 insert configuration

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m and special acme

Specification Data:

81349-dod-c-38999/20 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0