

View Online at <https://aerobasegroup.com/nsn/5935-01-261-4636>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand and right-hand

**Overall Length:**

0.663 inches

**Overall Height:**

0.440 inches

**Overall Width:**

0.406 inches

**Environmental Protection:**

Corrosion resistant and shock resistant and thermal shock resistant

**Threaded Device Type:**

Coupling facility and mounting hole

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Sma all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell and friction

**Thready Qty Per Inch (tpi):**

36 and 80

**Thread Size:**

0.250 inches and 0.060 inches

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification single treatment response all mating ends single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Passivate or gold

**Shell Surface Treatment Specification:**

Qq-p-35, type 1, 2, 3, 4 or 6 federal specification single treatment response or mil-g-45204 military specification single treatment response

**Insert Material Specification:**

Mil-p-19468 military specification single material response all mating ends or I-p-403 federal specification single material response all mating ends

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns and unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.