

View Online at <https://aerobasegroup.com/nsn/5935-01-261-4636>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Overall Length:

0.663 inches

Overall Height:

0.440 inches

Overall Width:

0.406 inches

Environmental Protection:

Corrosion resistant and shock resistant and thermal shock resistant

Threaded Device Type:

Coupling facility and mounting hole

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and friction

Thready Qty Per Inch (tpi):

36 and 80

Thread Size:

0.250 inches and 0.060 inches

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response all mating ends single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate or gold

Shell Surface Treatment Specification:

Qq-p-35, type 1, 2, 3, 4 or 6 federal specification single treatment response or mil-g-45204 military specification single treatment response

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends or I-p-403 federal specification single material response all mating ends

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.