

View Online at <https://aerobasegroup.com/nsn/5935-01-261-6372>

**Body Style:**

Straight shape

**Overall Length:**

2.295 inches

**Overall Height:**

0.874 inches

**Overall Width:**

0.614 inches

**Environmental Protection:**

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.150 inches

**Distance Between Mounting Facility Centers:**

1.993 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

25 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

425.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses

**Insert Material Specification:**

Mil-m-14, type sgd military specification all material responses single mating end

**Included Contact Quantity:**

25 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surface silver

**Precious Material And Weight:**

0.025 gold grains, troy and 0.025 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.