

View Online at <https://aerobasegroup.com/nsn/5935-01-261-7438>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.662 inches

**Overall Height:**

1.500 inches

**Overall Width:**

1.500 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.156 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.156 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.750 inches and 0.781 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-3 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

41.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

900.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1250.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

70.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Rubber synthetic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Included Contact Quantity:**

3 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.015 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

96906-ms3452 government standard

**Shelf Life:**

Nil

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.