Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-261-8411

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Rectangular shape center screwlock
Overall Length:
Between 1.665 inches and 1.685 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 1.295 inches and 1.305 inches
Overall Height:
1.520 inches
Overall Width:
Between 0.560 inches and 0.580 inches
Environmental Protection:
Corrosion resistant
Unthreaded Mounting Hole Diameter:
0.149 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
10 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Polarization boss
Connector Locking Method:
Screw
Thread Size:
0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end



Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.