

View Online at <https://aerobasegroup.com/nsn/5935-01-261-8431>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, rectangular

**Overall Length:**

0.829 inches

**Overall Height:**

2.390 inches

**Overall Width:**

2.875 inches

**Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.149 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

2.290 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.500 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

212 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

13.0 single mating end single contact grouping

**Polarization Method:**

Polarization boss

**Connector Locking Method:**

Jackscrew-socket

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade c military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sgd-f military specification single material response single mating end

**Included Contact Quantity:**

212 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.212 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Specification Data:**

81349-mil-c-28748/9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.