# NSN 5935-01-261-8444

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-261-8444

## Body Style:

Rectangular shape center screwlock

## **Overall Length:**

1.675 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.300 inches

## **Overall Height:**

1.070 inches

### **Overall Width:**

0.830 inches

## **Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

## Unthreaded Mounting Hole Diameter:

0.149 inches

## Mating End Quantity:

1

## Contact Position Arrangement Style:

20 single mating end

## Contact Removability:

Removable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

## **Polarization Method:**

Polarization boss

### **Connector Locking Method:**

Friction

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### Insert Material:

Plastic diallyl phthalate single mating end

## Contact Surface Treatment Specification:

Mil-g-45294 type 1, grade c military specification single treatment response single mating end single contact grouping

## Terminal Type:

Crimp single mating end single contact grouping

## Insert Material Specification:

Mil-m-14 ty sdg-f military specification single material response single mating end

## Included Contact Quantity:

20 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping



#### Precious Material And Location:

Contact surfaces gold

#### **Precious Material And Weight:**

0.020 gold grains, troy

### Precious Material:

Gold

#### Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-28748/9 government specification

Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

## Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45294 spec.