NSN 5935-01-261-9570

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-261-9570

Body Style:
Straight shape, external coupling
Overall Length:
1.328 inches
Overall Height:
0.609 inches
Overall Width:
0.609 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant
Unthreaded Mounting Hole Diameter:
Between 0.120 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.594 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.594 inches
Distance From Mounting Shoulder To Front Face:
Between 0.431 inches and 0.462 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
•
40394 single mating end
40394 single mating end
40394 single mating end Contact Removability:
40394 single mating end Contact Removability: Nonremovable single mating end single contact grouping
40394 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts:
40394 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping
40394 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Polarization Method:
40394 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway
40394 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg:
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 315.0
40394 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 315.0 Shell Type:
40394 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 315.0 Shell Type: Solid
40394 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 315.0 Shell Type: Solid Connector Locking Method:
40394 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 315.0 Shell Type: Solid Connector Locking Method: Bayonet pin

Copper alloy single mating end single contact grouping **Contact Surface Treatment:**

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-01-261-9570

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Shell Material Specification:
Qq-a-591 federal specification single material response
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.