Electrical Connector Backshell - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-261-9598

2b         Therefore:         Right-hand         Purshed Items:         Case witchin         Overall Length:         4.584 Inches         Overall Height:         15.682 Inches         Overall Height:         16.883 Inches         Overall Midthi:         1.688 Inches         6.000 Inches         7         1.000 Inches         6.000 Inches         6.000 Inches         7         1.000 Inches         1.100 Inche	Thread Class:
Right-hand         Right-hand         Furnished Items:         Dist cap wichain         Overall Length:         4.584 inches         Overall Height:         Between 1.542 inches and 1.572 inches         Overall Width:         1.688 inches         Attachment Feature Length:         4.684 viches         Cable Opening Diameter:         Between 0.444 inches and 0.562 inches         Cable Opening Quantity:         1         Star Designation:         22         Mounting Facility Type And Quantity:         1         1         Star Designation:         22         Mounting Facility Type And Quantity:         1         1         Star Designation:         24         Munimum alloy         StarLeas         StarLeas         Style Designator:         Style Designator:         Cadnium and chromate         Style Designator:         Style Designator:         Style Designator:         Style Designator:         Style Designator:         Style Designator:         Style Designator:<	2b
Fundamental formation           Dust cap wichain           Overall Length:           1.684 inclose           Overall Height:           Between 1.642 inclose and 1.672 incloses           Overall Width:           1.688 incloses           Overall Width:           1.688 incloses           Outcould Width:           1.688 incloses           Outcould Width:           1.688 incloses           Cable Opening Diameter:           Between 0.449 inclose and 0.582 incloses           Cable Opening Quantity:           1           Size Designation:           22           Mounting Facility Type And Quantity:           1           Threaded coupling           Threaded coupling           Mounting Facility Type And Quantity:           1           1           Threaded coupling           Munimum alloy           Site Designation:           23           1.375 inclose           Maerial:           Autonium and bromate           Sityle Designator:           Cachding and chromate           Sityle Designator:           Cachatim and chromate	Thread Direction:
Dust cap wichain         Verail Length:         4.54 inches         Verail Height:         Betwen 1.542 inches and 1.572 inches         Overail Width:         1.688 inches         Attachment Feature Length:         6.000 inches         Cable Opening Diameter:         Betwen 0.449 inches and 0.562 inches         Cable Opening Duantity:         1         Size Designation:         22         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Oty Per Inch (tpi):         18         Thread Size:         1.375 inches         Murinum alloy         Surface Treatment:         Caduum and chromate         Straight type wickable clamp         Surface Treatment:         Caduum and chromate         Straight type wickable clamp specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typica", "average", ", etc.).	Right-hand
Verail Length:         4.584 inches         Verail Wight:         Between 1.542 inches and 1.572 inches         Overail Wight:         1.688 inches         Attachment Feature Length:         1.680 inches         Cable Opening Diameter:         Between 0.449 inches and 0.562 inches         Cable Opening Quantity:         1         Stace Designation:         22         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Quy Per Inch (tpi):         18         Thread Size:         1.375 inches         Murinum alloy         Surface Treatment:         Caduium and chromate         Stright type wickele damp         Stright type wickele damp         Stright type wickele damp         Stright type wickele damp         Stright type wickele damp secification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification type data in specification type data on certain         environmental and performance requirements and test conditions that are shown as "typica", "etc.).	Furnished Items:
<ul> <li>4.584 inches</li> <li>Overall Height:</li> <li>Between 1.542 inches and 1.572 inches</li> <li>Overall Width: <ul> <li>1.688 inches</li> </ul> </li> <li>Attachment Feature Length:</li> <li>6.000 inches</li> </ul> <li>Cable Opening Diameter: <ul> <li>Between 0.449 inches and 0.562 inches</li> </ul> </li> <li>Cable Opening Quantity: <ul> <li>1</li> <li>Size Designation:</li> <li>22</li> </ul> </li> <li>Mounting Facility Type And Quantity: <ul> <li>1</li> <li>threadd coupling</li> <li>Threadd Size:</li> <li>1.375 inches</li> <li>Material:</li> <li>Aluminum alloy</li> <li>Surface Treatment:</li> <li>Cadvinum and chromate</li> <li>Straight type wickable clamp</li> <li>Surface Treatment:</li> <li>Cadvinum and chromate</li> <li>Straight type wickable clamp</li> <li>Surface Treatment:</li> <li>Cadvinum and chromate</li> <li>Straight type wickable clamp</li> <li>Surface Treatment:</li> <li>Cadvinum and chromate</li> <li>Straight type wickable clamp</li> <li>Surface Treatment:</li> <li>Cadvinum and chromate</li> <li>Straight type wickable clamp</li> <li>Surface Treatment:</li> <li>Cadvinum and chromate</li> <li>Straight type wickable clamp</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Tet Data Documenti</li> <li>8149-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmential and performance requirements and test conditions that are shown as "typical", "average", ", etc.).</li> </ul> </li>	Dust cap w/chain
Overall Height:         Between 1.542 inches and 1.572 inches         Overall Width:         1.688 inches         Attachment Feature Length:         6.000 inches         Cable Opening Diameter:         Between 0.449 inches and 0.552 inches         Cable Opening Quantity:         1         Size Designation:         22         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Cuy Per Inch (tpi):         18         Thready Size:         1.375 inches         Material:         Aturinum alloy         Style Designation:         Signator:         Style Designation:         Style Designation:         Style Designato:         Strafee Treatment:         Cadmium and chromate         Thread Stole specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in spe	Overall Length:
Between 1.542 inches and 1.572 inches         Overall Width:         1.688 inches         Attachment Feature Length:         6.000 inches         Cable Opening Diameter:         Between 0.449 inches and 0.562 inches         Cable Opening Quantity:         1         Size Designation:         22         Mounting Facility Type And Quantity:         1         12         Mounting Facility Type And Quantity:         1         1         Thready Cuy Per Inch (tpl):         18         Thready Size:         1.375 inches         Material:         Aduminum alloy         Surface Treatment:         Cadmium and chromate         Straignt type wicable clamp         Surface Treatment:         Cadmium and chromate         Straignt type wicable clamp         Thread Straignator:         Straignt type wicable clamp         Straignt type wicable clamp         Straignt type wicable cl	4.584 inches
Overall Width:         1.688 inches         Attachment Feature Length:         6.000 inches         Cable Opening Diameter:         Between 0.449 inches and 0.562 inches         Cable Opening Quantity:         1         Size Designation:         22         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         18         Thready Qty Per Inch (tpi):         18         Mutninum alloy         Surface Treatment:         Cathilum and chromate         Style Designator:         Straight type wicable clamp         Mutninum alloy         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type wicable clamp         Wordson         Surface Treatment:         Cadmium and chromate         Straight type wicable clamp         Surface Treatment:         Cadmium and chromate         Straight type wicable clamp         Wordson         Straight type wicable clamp         Treat Data Documenti         Gadmium and chromate         Tere Data Documenti	Overall Height:
<ul> <li>1.688 inches</li> <li>Attachment Feature Length:</li> <li>6.000 inches</li> <li>6.000 inches</li> <li>Gable Opening Diameter:</li> <li>Between 0.449 inches and 0.562 inches</li> <li>Gable Opening Quantity:</li> <li>1</li> <li>Size Designation:</li> <li>22</li> <li>Mounting Facility Type And Quantity:</li> <li>1 threaded coupling</li> <li>Thready Qty Per Inch (tpl):</li> <li>18</li> <li>Thready Qty Per Inch (tpl):</li> <li>13</li> <li>Thread Size:</li> <li>1.375 inches</li> <li>Material:</li> <li>Autinium alloy</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Style Designator:</li> <li>Straight type wicable clamp</li> <li>Straight type wicable clamp</li> <li>Straight type wicable clamp</li> <li>Straight type wicable clamp</li> <li>Strates Treatment:</li> <li>Attachment Height Strates</li> <li>Attachment Height Strates</li> <li>Straight type wicable clamp</li> <li>Strates Treatment:</li> <li>Attachment Height Strates</li> <li>Attachment Height Strates</li> <li>Attachment Height Strates</li> <li>Attachment Height Height</li></ul>	Between 1.542 inches and 1.572 inches
Attachment Feature Length:         6.000 inches         Cable Opening Diameter:         Between 0.449 inches and 0.562 inches         Cable Opening Quantity:         1         Size Designation:         22         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         18         Thread Size:         1.375 inches         Material:         Aluminum alloy         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type wicable clamp         Material:         Bathact Treatment:         Cadmium and chromate         Style Designator:         Straight type wicable clamp         Straight type wicable clamp         Bathact Treatment:         Cadmium and chromate         Test Data Document         Bathact Stole Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain         environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).         Thread Series Designator:	Overall Width:
<ul> <li>6.000 inches</li> <li>Cable Opening Diameter:</li> <li>Between 0.449 inches and 0.562 inches</li> <li>Cable Opening Quantity: <ol> <li>Stree Designation:</li> </ol> </li> <li>Stree Designation:</li> <li>Stree Designation:</li> <li>Mounting Facility Type And Quantity: <ol> <li>thready Guy Per Inch (pi):</li> <li>thready Guy Per Inch (pi):</li> <li>Thread Size: <ol> <li>.375 inches</li> </ol> </li> <li>Material: <ol> <li>Aluminum alley</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Streight type w/cable clamp</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Thread Size:</li> <li>Straight type surfaction (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).</li> </ol> </li> </ol></li></ul>	1.688 inches
Cable Opening Diameter:         Between 0.449 inches and 0.562 inches         Cable Opening Quantity:         1         Size Designation:         22         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpl):         18         Thread Size:         1.375 inches         Material:         Aluminum alloy         Surface Treatment:         Cadinium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Thread Stata Document:         Bating Stata Document:         Cadmium and chromate         Test Data Document:         B1349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).         Thread Series Designator:	Attachment Feature Length:
Between 0.449 inches and 0.562 inches         Cable Opening Quantity:         1         Size Designation:         22         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         18         Thread Size:         1.376 inches         Material:         Aluminum alloy         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).         Thread Series Designator:	6.000 inches
Cable Opening Quantity:         1         Size Designation:         22         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         18         Thread Size:         1.375 inches         Material:         Aluminum alloy         Surface Treatment:         Cadmium and chromate         Straight type w(cable clamp)         Straight type w(cable clamp)         Surface Treatment:         Cadmium and chromate         Straight type w(cable clamp)         Surface Treatment:         Cadmium and chromate         Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Thread Series Designator:	Cable Opening Diameter:
1         Size Designation:         22         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         18         Thread Size:         1.375 inches         Material:         Aluminum alloy         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.).         Thread Series Designator:	Between 0.449 inches and 0.562 inches
Size Designation:         22         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         18         Thread Size:         1.375 inches         Material:         Aluminum alloy         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).         Thread Series Designator:	Cable Opening Quantity:
22         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         18         Thread Size:         1.375 inches         Material:         Aluminum alloy         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Straight type w/cable clamp         Surface Treatment:         Reade Study Straight type w/cable clamp         Surface Treatment:         Readmium and chromate         Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).         Thread Series Designator:	1
<ul> <li>Mounting Facility Type And Quantity:         <ul> <li>threaded coupling</li> </ul> </li> <li>Thready Qty Per Inch (tpi):         <ul> <li>thready Qty Per Inch (tpi):</li> <li>thread Size:</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Surface Treatment:</li> <li>thread Size:</li> <li>thread Series Designator:</li> <li>thread Series Designator:</li> <li>thread Series Designator:</li> </ul> </li> </ul>	Size Designation:
1 threaded coupling         Thready Qty Per Inch (tpi):         18         Thread Size:         1.375 inches         Material:         Aluminum alloy         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Bita49-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Thread Series Designator:	22
<ul> <li>Thready Qty Per Inch (tpi):         <ul> <li>18</li> </ul> </li> <li>Thread Size:             <ul> <li>1.375 inches</li> <li>Material:</li></ul></li></ul>	Mounting Facility Type And Quantity:
<ul> <li>18</li> <li>Thread Size:</li> <li>1.375 inches</li> <li>Material:</li> <li>Aluminum alloy</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Style Designator:</li> <li>Straight type w/cable clamp</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Test Data Document:</li> <li>81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).</li> <li>Thread Series Designator:</li> </ul>	1 threaded coupling
<ul> <li>Thread Size:</li> <li>1.375 inches</li> <li>Material:</li> <li>Aluminum alloy</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Style Designator:</li> <li>Straight type w/cable clamp</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Surface Treatment:</li> <li>Batriaght type w/cable clamp</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Trest Data Document:</li> <li>81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).</li> <li>Thread Series Designator:</li> </ul>	Thready Qty Per Inch (tpi):
<ul> <li>1.375 inches</li> <li>Material:</li> <li>Aluminum alloy</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Style Designator:</li> <li>Straight type w/cable clamp</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Test Data Document:</li> <li>81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).</li> </ul>	18
Material:Aluminum alloySurface Treatment:Cadmium and chromateStyle Designator:Straight type w/cable clampSurface Treatment:Cadmium and chromateSurface Treatment:Cadmium and chromateTest Data Document:81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificationformat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).Thread Series Designator:	Thread Size:
Aluminum alloy         Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Thread Series Designator:	1.375 inches
Surface Treatment:         Cadmium and chromate         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Thread Series Designator:	Material:
<ul> <li>Cadmium and chromate</li> <li>Style Designator:</li> <li>Straight type w/cable clamp</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Test Data Document:</li> <li>81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).</li> <li>Thread Series Designator:</li> </ul>	Aluminum alloy
Style Designator:         Straight type w/cable clamp         Surface Treatment:         Cadmium and chromate         Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Thread Series Designator:	Surface Treatment:
<ul> <li>Straight type w/cable clamp</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Test Data Document:</li> <li>81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).</li> <li>Thread Series Designator:</li> </ul>	Cadmium and chromate
Surface Treatment:         Cadmium and chromate         Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Thread Series Designator:	Style Designator:
Cadmium and chromate <b>Test Data Document:</b> 81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). <b>Thread Series Designator:</b>	Straight type w/cable clamp
<b>Test Data Document:</b> 81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). <b>Thread Series Designator:</b>	Surface Treatment:
81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Cadmium and chromate
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator:	81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Thread Series Designator:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unef	Thread Series Designator:
	Unef

Specification Data:

81349-mil-c-85049/5 government specification

Shelf Life:

N/a

Electrical Connector Backshell - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A10100