## NSN 5935-01-262-0906

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-262-0906

**Body Style:** Straight shape **Overall Length:** 5.094 inches **Overall Height:** 0.609 inches **Overall Width:** 0.438 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Distance Between Mounting Facility Centers: 4.688** inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Shell Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic mineral filled single mating end and plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:** 

Cadmium

## NSN 5935-01-262-0906

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-14, type mdg military specification all material responses single mating end

**Shell Guide Type And Location Designator:** 

B slot and k slot

**Included Contact Quantity:** 

35 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.035 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.