Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-262-0915

ody Style:	
traight shape duplex	
verall Width:	
.750 inches	
ody Length:	
.875 inches	
nvironmental Protection:	
leat resistant and salt water resistant	
istance Between Mounting Facility Centers: .281 inches	
lating End Quantity:	
Contact Resition Arrangement Styles	
Contact Position Arrangement Style:	
all mating ends	
ontact Removability:	
onremovable all mating ends all contact groupings	
Contact Maximum Current Rating In Amps:	
5.0 all mating ends all contact groupings	
contact Maximum Ac Voltage Rating In Volts:	
27.0 all mating ends all contact groupings olarization Method:	
contact	
connector Locking Method:	
riction	
erminal Location:	
ide all mating ends all contact groupings	
opper alloy all mating ends all contact groupings	
erminal Type:	
crew all mating ends all contact groupings est Data Document:	
	on format:
1348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
xcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environ	imentai
nd performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
pecification Data:	
1348-w-c-596/112 government specification	
helf Life:	
nit Of Measure:	
emilitarization:	

A039b0