

View Online at <https://aerobasegroup.com/nsn/5935-01-262-0921>

**Body Style:**

Straight type

**Overall Length:**

6.100 inches

**Overall Height:**

Between 0.410 inches and 0.440 inches

**Overall Width:**

0.500 inches

**Environmental Protection:**

Humidity resistant and corrosion resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.068 inches and 0.072 inches

**Distance Between Mounting Facility Centers:**

Between 5.797 inches and 5.803 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Pin single mating end single contact grouping

**Insert Material Specification:**

Mil-p-46161, grade b, cl 30 military specification single material response single mating end or mil-m-24519, type gpt-30f military specification single material response single mating end

**Included Contact Quantity:**

112 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.112 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-p-46161 spec.