

View Online at <https://aerobasegroup.com/nsn/5935-01-262-2528>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Hood, top opening w/clamp

Overall Length:

Between 2.620 inches and 2.650 inches

Overall Height:

2.000 inches

Overall Width:

0.700 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Cable Entrance Diameter:

Between 0.391 inches and 0.421 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

50 single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Hood, top opening

Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Cable clamp

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Metal

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

Insert Material Specification:

Mil-m-14, ty gdi-30 or sd6f military specification all material responses single mating end

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.050 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.