## NSN 5935-01-262-2537

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-262-2537

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.000 inches

**Overall Height:** 

0.870 inches

**Cable Entrance Diameter:** 

0.120 inches

**Threaded Device Type:** 

Mounting bushing

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Bnc single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Connector Cable Strain Relief Method:** 

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, grade c, cl 00 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-530 federal specification single material response single mating end single contact grouping

**Shell Material:** 

Copper alloy

**Shell Material Specification:** 

Qq-b-626 federal specification single material response

## NSN 5935-01-262-2537

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

L-p-403 federal specification single material response single mating end

## **Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/flat

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surface gold

**Precious Material And Weight:** 

0.005 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.