

View Online at <https://aerobasegroup.com/nsn/5935-01-262-2896>

**Body Style:**

Angle shape

**Overall Length:**

3.500 inches

**Overall Height:**

0.675 inches

**Overall Width:**

0.280 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

750.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy 510 single mating end single contact grouping

**Contact Surface Treatment:**

Tin single mating end single contact grouping and lead single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-p-81728 military specification 1st treatment response single mating end single contact grouping and mil-p-81728 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550, class 4 military specification 3rd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-w-321 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-46161, grade b, class 30 military specification single material response single mating end

**Included Contact Quantity:**

50 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Shelf Life:**

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-p-81728 spec.