NSN 5935-01-262-2898

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-262-2898

Body Style:

Straight shape, internal coupling

Overall Length:

0.790 inches

Overall Diameter:

0.190 inches

Environmental Protection:

Corrosion resistant and shock resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

12400.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Shrinkable tubing

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, gr a military specification 1st treatment response single mating end single contact grouping and mil-c-14550, cl 4

military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy 360

Shell Surface Treatment:

Gold

NSN 5935-01-262-2898

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment Specification: Mil-g-45204 military specification single treatment response **Shell Material Specification:** Qq-b-626 federal specification single material response **Insert Material Specification:** L-p-403 federal specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact and shell surfaces gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.