

View Online at <https://aerobasegroup.com/nsn/5935-01-262-3575>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

60.0 millimeters

Overall Diameter:

39.9 millimeters

Environmental Protection:

Fuel resistant and shock resistant and vibration resistant and waterproof

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

20-21 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

41.0 single mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Thready Qty Per Inch (tpi):

18

Thread Size:

1.188 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Silver single mating end all contact groupings or gold single mating end all contact groupings or rhodium single mating end all contact groupings

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification 1st treatment response single mating end all contact groupings or mil-g-45204 military specification 2nd treatment response single mating end all contact groupings or mil-f-14072 military specification 2nd treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type ii, cl 2 federal specification all treatment responses

Included Contact Quantity:

8 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces silver or contact surfaces gold or contact surfaces rhodium

Precious Material And Weight:

0.013 silver grains, troy or 0.013 gold grains, troy or 0.013 rhodium grains, troy

Precious Material:

Silver or gold or rhodium

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.