

View Online at <https://aerobasegroup.com/nsn/5935-01-262-4752>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Overall Length:**

0.575 inches

**Overall Height:**

0.480 inches

**Overall Width:**

0.188 inches

**Environmental Protection:**

Corrosion resistant and thermal shock resistant and shock resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.092 inches and 0.096 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.328 inches

**Distance From Mounting Shoulder To Front Face:**

0.310 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

335.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.190 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Metal

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.