NSN 5935-01-262-5877

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-262-5877 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.593 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.281 inches **Overall Width:** 1.110 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 0.766 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 75 single mating end **Contact Removability:** Nonremovable single mating end 1st contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end 1st contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end 1st contact grouping **Contact Material:** Copper alloy single mating end 1st contact grouping **Contact Surface Treatment:** Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Criticality Code Justification:**

Feat

NSN 5935-01-262-5877

A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end 1st contact grouping
Unable To Decode:
Unable to decode and unable to decode and unable to decode and unable to decode
Included Contact Quantity:
61 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end 1st contact grouping
Special Features:
14 contacts omitted
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.061 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: