## NSN 5935-01-262-6806

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-262-6806 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Height:** 2.282 inches **Overall Width:** 2.500 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.938 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.938 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 36-5 single mating end **Contact Maximum Current Rating In Amps:** 245.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 16 **Thread Size:** 2.250 inches **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:** 4 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Test Data Document:** 81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Un

N/a

Shelf Life:

## NSN 5935-01-262-6806

Electrical Receptacle Connector - Page 2 of 2



Unit	Of	Measure:
------	----	----------

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.