## NSN 5935-01-262-6816

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-262-6816

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.100 inches

**Overall Height:** 

Between 1.562 inches and 1.582 inches

Overall Width:

Between 1.562 inches and 1.582 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.123 inches and 0.138 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.785 inches and 0.790 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

21-39 single mating end

**Contact Removability:** 

Removable single mating end all contact groupings

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

342.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end all contact groupings

**Terminal Type:** 

Crimp single mating end all contact groupings

**Shell Material:** 

Aluminum alloy

## NSN 5935-01-262-6816

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
37 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.047 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27505 government standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.