Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-262-9055

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.590 inches

Overall Height:

0.312 inches

Overall Width:

0.450 inches

Environmental Protection:

Corrosion resistant and shock resistant and vibration resistant and thermal shock resistant and moisture resistant and fungus resistant

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

2.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

End Application:

Aircraft, f-16

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end and plastic polytetrafluoroethylene single mating end



NSN 5935-01-262-9055 Electrical Receptacle Connector - Page 2 of 2 **Contact Surface Treatment Specification:** Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping **Criticality Code Justification:** Feat **Terminal Type:** Crimp single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Shell Material:** Steel comp 303 and copper alloy **Shell Surface Treatment:** Gold or nickel or passivate Shell Surface Treatment Specification: Mil-g-45204 military specification 1st treatment response **Shell Material Specification:** Astm a582, cond a assn standard 1st material response and qq-c-530 federal specification 2nd material response **Insert Material Specification:** L-p-403, type 1 federal specification all material responses single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/double flat **Included Contact Type:** Coaxial socket single mating end single contact grouping **Special Features:** Weapon system essential **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.001 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns Shelf Life: N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.