NSN 5935-01-262-9710

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-262-9710

Body Style:
Straight shape
Overall Length:
0.954 inches
Overall Height:
3.110 inches
Overall Width:
2.000 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.783 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.436 inches
Distance From Mounting Shoulder To Front Face:
0.756 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
67 1st mating end
Contact Removability:
Removable all mating ends all contact groupings
Contact Maximum Current Rating In Amps:
7.5 1st mating end 2nd contact grouping
Polarization Method:
Mating end and 3 polarization posts
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Gold all mating ends all contact groupings and nickel all mating ends all contact groupings
Insert Material:
Plastic diallyl phthalate all mating ends
Contact Surface Treatment Specification:
Mil-g-45204, type 1, gr c, cl 5 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal
specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp all mating ends all contact groupings

NSN 5935-01-262-9710

Electrical Receptacle Connector - Page 2 of 2



Guide Design And Location:

Hexagon shape male post left-hand at 12 oclock and hexagon shape male post center at 12 oclock and hexagon shape male post right-hand at 12 oclock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Shell Material Specification:

Qq-a-591, comp a federal specification single material response

Insert Material Specification:

Mil-m-14, ty gdi-30f or sdg-f military specification single material response all mating ends

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.173 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.