## NSN 5935-01-262-9927

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-262-9927 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Overall Length:** 1.250 inches **Overall Diameter:** 0.500 inches **Threaded Device Type:** Back shell and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Removable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 32 and 32 **Thread Size:** 0.375 inches and 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** 

Nickel

**Included Contact Quantity:** 

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round

## NSN 5935-01-262-9927

Electrical Receptacle Connector - Page 2 of 2



Inc	luded	Contact	Type
inc	luaea	Contact	туре

Coaxial socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.005 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unef and unef

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0