

View Online at <https://aerobasegroup.com/nsn/5935-01-263-1865>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Rectangular shape center screwlock

**Overall Length:**

2.780 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.460 inches

**Overall Height:**

0.863 inches

**Overall Width:**

0.725 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

88 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1200.0 single mating end single contact grouping

**Polarization Method:**

Polarization boss

**Connector Locking Method:**

Jackscrew

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyester single mating end and glass single mating end

**Contact Surface Treatment Specification:**

Mil-g-42204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626, comp 2 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-p-46161, grade b, class 3 military specification 1st material response single mating end

**Included Contact Quantity:**

88 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.088 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-42204 spec.