NSN 5935-01-263-1866

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-263-1866

view Online at https://aerobasegroup.com/nsn/5935-01-263-1666
Body Style:
Straight shape
Overall Length:
0.984 inches
Overall Height:
3.937 inches
Overall Width:
3.375 inches
Unthreaded Mounting Hole Diameter:
Between 0.138 inches and 0.145 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
3.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.359 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Mating End Quantity:
2
Contact Removability:
Nonremovable all mating ends all contact groupings
Contact Maximum Current Rating In Amps:
80.0 all mating ends 1st contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Gold all mating ends all contact groupings and nickel all mating ends all contact groupings or copper all mating ends all contact groupings
Insert Material:
Plastic diallyl phthalate all mating ends or plastic melamine all mating ends
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response all mating ends all contact groupings
Terminal Type:
Solder well all mating ends all contact groupings
Contact Material Specification:

Aluminum alloy 380.0

Shell Material:

Qq-c-533 federal specification single material response all mating ends all contact groupings

NSN 5935-01-263-1866

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-m-14, ty sdg-f or gdi-30f military specification 1st material response all mating ends or mil-m-14, cmg military specification 2nd material
response all mating ends
Included Contact Type:
Round pin all mating ends all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.052 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.