NSN 5935-01-263-1870

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-263-1870 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.312 inches **Overall Height:** 0.859 inches **Overall Width:** 0.625 inches **Distance Between Mounting Facility Centers:** 1.000 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 9 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 2180.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 3050.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Thready Qty Per Inch (tpi): 40 **Thread Size:**

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-263-1870

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic melamine mineral filled single mating end
Terminal Type:
Solder well single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0