

View Online at <https://aerobasegroup.com/nsn/5935-01-263-1871>

**Body Style:**

Straight shape

**Overall Length:**

1.075 inches

**Overall Height:**

0.629 inches

**Overall Width:**

0.298 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.088 inches and 0.094 inches

**Distance Between Mounting Facility Centers:**

0.865 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

21 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

400.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyphenylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, ty ii, grade c, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type ii federal specification single treatment response

**Insert Material Specification:**

Mil-p-46174 military specification single material response single mating end

**Included Contact Quantity:**

21 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.021 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.