

View Online at <https://aerobasegroup.com/nsn/5935-01-263-5057>

**Body Style:**

Angle shape w/cable clamp

**Overall Diameter:**

3.312 inches

**Body Angle In Deg:**

90.0

**Environmental Protection:**

Heat resistant and salt water resistant

**Cable Entrance Diameter:**

Between 1.070 inches and 1.380 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

18-30 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

60.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 single mating end all contact groupings

**Polarization Method:**

Contact

**Connector Cable Strain Relief Method:**

Cable clamp

**Distance From Centerline To Cable End:**

2.844 inches

**Terminal Location:**

Side single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Terminal Type:**

Screw single mating end all contact groupings

**Included Contact Quantity:**

3 single mating end 2nd contact grouping

**Included Contact Type:**

U-pin single mating end 1st contact grouping

**Test Data Document:**

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81348-w-c-596/63 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0