NSN 5935-01-263-5082



Electrical Receptable Confidencial - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5935-01-263-5082	
Body Style:	
Straight shape	
Overall Length:	
1.340 inches	
Overall Height:	
Between 1.178 inches and 1.198 inches	
Overall Width:	
4.296 inches	
Environmental Protection:	
Corrosion resistant and moisture resistant and shock resistant and vibration resistant	
Unthreaded Mounting Hole Diameter:	
Between 0.280 inches and 0.285 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
Between 0.558 inches and 0.566 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
3.875 inches	
Distance From Mounting Shoulder To Front Face:	
0.551 inches	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
77 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Polarization Method:	
Mating end	
Shell Type:	
Solid	
Connector Locking Method:	
Friction	

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-263-5082

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Shell Material Specification:
Qq-a-36, t6 federal specification single material response
Included Contact Quantity:
65 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.077 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26518 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27399 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.