

View Online at <https://aerobasegroup.com/nsn/5935-01-263-5082>

**Body Style:**

Straight shape

**Overall Length:**

1.340 inches

**Overall Height:**

Between 1.178 inches and 1.198 inches

**Overall Width:**

4.296 inches

**Environmental Protection:**

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.280 inches and 0.285 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.558 inches and 0.566 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

3.875 inches

**Distance From Mounting Shoulder To Front Face:**

0.551 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

77 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy 6061

**Shell Surface Treatment:**

Anodize

**Shell Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Shell Material Specification:**

Qq-a-36, t6 federal specification single material response

**Included Contact Quantity:**

65 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.077 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-26518 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

96906-ms27399 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.