Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-263-9277

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

3.679 inches

Overall Height:

2.188 inches

Overall Width:

2.188 inches

Environmental Protection:

Salt water resistant and heat resistant and cold resistant and vibration resistant and humidity resistant and thermal shock resistant and fuel resistant and shock resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

0.199 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.688 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.688 inches

Distance From Mounting Shoulder To Front Face:

2.504 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

B4s single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

90.0 and 270.0

End Application:

Cable conn adapt set

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Metal single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-01-263-9277

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:CadmiumShell Surface Treatment Specification:Qq-p-416, type ii, class 2 federal specification single treatment responseIncluded Contact Quantity:4 single mating end single contact groupingIncluded Contact Type:Round pin single mating end single contact groupingPrecious Material And Location:Contact surfaces goldPrecious Material:GoldShelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.