

View Online at <https://aerobasegroup.com/nsn/5935-01-263-9593>

Body Style:

Straight shape, internal coupling

Overall Length:

Between 0.995 inches and 1.035 inches

Overall Diameter:

0.312 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Tnc all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Frequency Rating:

26500.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and internally threaded coupling nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification single treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530, con h federal specification single material response all mating ends single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26704 military specification single treatment response

Shell Material Specification:

Qq-s-763 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Round socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.