## NSN 5935-01-263-9594

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-263-9594

<b>Body</b>	Style:
-------------	--------

Straight edge type w/mounting flange

**Overall Length:** 

1.842 inches

**Overall Height:** 

0.460 inches

**Overall Width:** 

0.343 inches

#### **Environmental Protection:**

Heat resistant and cold resistant and corrosion resistant

#### **Unthreaded Mounting Hole Diameter:**

0.128 inches

#### **Distance Between Mounting Facility Centers:**

1.532 inches

#### **Board Accommodated Length:**

1.100 inches single board

#### **Board Accommodated Width:**

0.078 inches

## **Mating End Quantity:**

1

## **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

## **Contact Maximum Ac Voltage Rating In Volts:**

2000.0 single mating end single contact grouping

#### **Polarization Method:**

Mating end

## **Connector Locking Method:**

Friction

## **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## Insert Material:

Plastic diallyl phthalate single mating end

#### **Terminal Type:**

Wire wrap single mating end single contact grouping

# NSN 5935-01-263-9594

Electrical Receptacle Connector - Page 2 of 2



## **Contact Material Specification:**

Qq-b-750, composition a federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

Mil-m-14f, type sdg-f military specification single material response single mating end

## **Included Contact Quantity:**

12 single mating end single contact grouping

## **Included Contact Type:**

Bifurcated spring single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.012 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14f spec.