

View Online at <https://aerobasegroup.com/nsn/5935-01-264-0133>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

33.8 millimeters

Overall Height:

38.0 millimeters

Overall Width:

38.0 millimeters

Environmental Protection:

Fuel resistant and shock resistant and vibration resistant and waterproof

Unthreaded Mounting Hole Diameter:

Between 3.05 millimeters and 3.2 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

29.4 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

29.4 millimeters

Distance From Mounting Shoulder To Front Face:

19.0 millimeters

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

20-3 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

41.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Thread Qty Per Inch (tpi):

18

Thread Size:

1.125 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping and gold single mating end single contact grouping and rhodium single mating end single contact grouping

Insert Material:

Rubber synthetic single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification 1st treatment response single mating end single contact grouping and mil-g-45204 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416 c cl 2, ty2 federal specification all treatment responses

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver and contact surfaces gold and contact surfaces rhodium

Precious Material And Weight:

0.015 silver grains, troy and 0.015 gold grains, troy and 0.015 rhodium grains, troy

Precious Material:

Silver and gold and rhodium

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A0001-0

Mil-std (military Standard):

Mil-g-45204 spec.